

Rinnai

HEATERS WATER HEATERS FIREPLACES

IMAGINE THE COMFORT OF DUCTLESS ZONE HEATING.

— Not Just Heat... Comfortable Heat.

A man and a woman are lying on a white fur rug, smiling warmly at the camera. They are positioned next to two white, rectangular Rinnai ductless zone heaters. The woman is on the left, resting her chin on her hand, and the man is on the right, leaning forward. The heaters are in the foreground, partially obscuring the rug. The background is a soft, out-of-focus indoor setting.

**ASK ABOUT THE
RCE-590 PLASMA
WITH AIR-CLEANING
TECHNOLOGY**

Please visit www.rinnai.us
for more product information

The Benefits of Rinnai Heaters



MODEL RCE-329/RCE-429 & RCE-229

Optional Custom Wall Mounting Kit
Allows RCE-329/RCE-429 and RCE-229 to be wall mounted.



MODEL RCE-606A, RCE-606TRA-II

Remote Control and dual on-off programming
on the 606TRA-II model.



UP TO 99.9% EFFICIENT HEAT EXCHANGER

- The Ductless Zone Heater's reputation lies in its vent-free system. Just imagine, no heat loss from leaky ducts as well as an easy installation.

ADVANCED SAFETY FEATURES

- The first "cool-to-the-touch cabinet" in America
- Child safety lock
- Electronic ignition—no pilot light
- Digital, adaptive control
- On board self-diagnostics for easier maintenance
- Earthquake proof - tilt-switch
- Each heater passes a rigorous battery of factory tests

INNOVATIVE MODULATING GAS VALVE AND BLOWER

- Whisper quiet 7-stage fully modulating blower—no more going from on to off and hot to cold
- Automatically adjusts the heat output and blower control, delivering a stable room temperature for maximum efficiency and comfort

UNBEATABLE WARRANTY

- 3 year warranty on all parts and labor.

PRODUCT APPLICATIONS

- Enjoy comfortable heat in any type of apartment suite, room addition, condo, basement, sunroom, hallway or bathroom.

ACCESSORIES

ACCESSORIES FOR VENT-FREE HEATER

RC-229-550 (Wall mounting bracket for RCE-229)
RC-329-550 (Wall mounting bracket for RCE-329 & RCE-429)

SPECIFICATIONS

MODEL	CFMS	AMPERAGE	DECIBELS	BTU HIGH	BTU LOW	DIMENSIONS	APPLICATION
RCE 229 A	64 High 46 Low	33 Watts	High=38dBA Low=28dBA	6,000 NG 6,000 LP	2,000 NG 2,500 LP	H 14 9/16" W 14 3/4" D 6 11/16"	Bathroom
RCE 329 A	92 High 53 Low	27 Watts	High=38dBA Low=28dBA	10,000 NG 10,000 LP	3,000 NG 3,400 LP	H 17 7/16" W 16 9/16" D 8"	Bedroom
RCE 429 A	106 High 64 Low	29 Watts	High=41dBA Low=31dBA	14,000 NG 14,000 LP	4,000 NG 5,200 LP	H 17 7/16" W 16 9/16" D 8"	Medium Room
RCE 606 A	198 High 99 Low	40 Watts	High=42dBA Low=26dBA	24,000 NG 21,000 LP	5,000 NG 5,500 LP	H 17 1/2" W 22 1/2" D 7 3/4"	Large Room
RCE 606 TRA-II	198 High 99 Low	45 Watts	High=40dBA Low=28dBA	24,000 NG 21,000 LP	5,000 NG 5,500 LP	H 17 1/2" W 22 1/2" D 7 3/4"	Large Room

Rinnai is continually updating and improving products, therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation. See owners manual for complete specifications.